



SET-UP SHEET

NAME Mills Pond RACE _____ DATE _____
 TRACK _____ CITY/COUNTRY _____ TRACK CONDITION _____

AIR TEMP F C
 LAPS _____
 BEST LAP TIME _____ in LAP
 TRACK SIZE
 OPEN MEDIUM TIGHT
 TRACK TRACTION
 HIGH MEDIUM LOW

DIFFERENTIAL OIL

FRONT	CENTER	REAR
7K	5K	3K

CLUTCH

SHOE BRAND IGT8
 COMPOUND ALUM CARBON
 SPRING BRAND IGT8
 TENSION 0.8 mm
 CLUTCH SHOES 4 SHOE

GEARING

SPUR GEAR	48	T
PINION GEAR	14	T

TIRES

FRONT TYPE Gridiron
 COMPOUND Soft
 INSERT FOAM Red
 REAR TYPE Gridiron
 COMPOUND Soft
 INSERT FOAM Red

ENGINE

TYPE Mantra
 PORT 4 Port
 PLUG CT06
 NORMAL TURBO
 HEAD CLEARANCE _____
 PIPE
 9901/41021
 FUEL BRAND _____

FRONT

1 2 3 4 5 6

STEERING BAR
 A B C

1 2

1 2 3 4 5

1 2

INSERT NR. 0.5

SWAY BAR 2.3
 HEX Std

CASTER BLOCK
 PLASTIC ALUM

STEERING KNUCKLE ARM
 PLASTIC ALUM

CASTER BLOCK ANGLE
 10
 12
 14

SHOCK

FRONT

SHOCK LENGTH 117 mm
 OIL wt. 350
 PISTON 1.4
 SPRING Red

SHOCK LENGTH

RIDE HEIGHT 28 mm
 DROOP 102.5 mm
 CAMBER ANGLE 2 °
 TOE ANGLE 2 °

PLASTIC ALUM

REAR

1 2 3 4 5 6

1 2

1 2

1 2 3

1 2

INSERT NR. 3.3

SWAY BAR 2.3
 HEX Std

WHEEL HUB
 PLASTIC ALUM

SUSPENSION ARM
 FORWARD BACK

SHOCK

REAR

SHOCK LENGTH 132.5 mm
 OIL wt. 350
 PISTON 1.4
 SPRING Red

SHOCK LENGTH

RIDE HEIGHT 28 mm
 DROOP 25.5 mm
 CAMBER ANGLE 2 °

PLASTIC ALUM

WHEELBASE SHIMS
 0mm 2mm
 2.5mm 4.5mm